

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A circuit for dividing periodic input pulses by a preset integer M, comprising:

a dual modulus prescaler arranged to receive periodic input pulses and to count the received input pulses for generating prescaled pulses, wherein one prescaled pulse is generated for every Qth input pulse, wherein Q is a division modulus having a value depending on a value of a modulus control signal, wherein when a prescaled pulse is generated from a selected input pulse, the modulus control signal is ignored at least until the onset of a next input pulse is received; ~~and~~

a swallow counter arranged to change the modulus control signal to a different value in response to the prescaler receiving every Mth input pulse, wherein M is a preset integer; and

a program counter to generate a reset signal in response to the prescaler receiving the Mth input pulse, and

wherein the swallow counter changes the modulus control signal in response to the reset signal.

2. (Original) The circuit of claim 1, wherein

if the ignored modulus control signal acquires a different value due to the selected input pulse, the next pulse is counted according to a correspondingly different value of Q.

3. (Original) The circuit of claim 2, wherein

when the prescaler receives a selected one of the Mth pulses, the modulus control signal changes value after the prescaler has already received the onset of a next input pulse.

4. (Original) The circuit of claim 1, wherein

the prescaler includes an OR gate for ORing the modulus control signal with another signal.

Claim 5 (canceled)

6. (Currently amended) The circuit of claim 51, further comprising:
a frequency/phase detector arranged to receive a divided down signal generated in response to the prescaler receiving the Mth input pulse, and to output a synchronized signal in response to the divided down signal; and
a fast clock generator to generate a fast clock signal from the synchronized signal, and
wherein the input pulses are derived from the fast clock signal.
7. (Currently amended) The circuit of claim 51, wherein
the program counter is adapted to generate the reset signal in response to receiving a prescaled pulse that corresponds to the prescaler receiving the Mth input pulse.
8. (Original) The circuit of claim 7, wherein
the prescaler includes components that define state variables which are initialized to particular values when a prescaled pulse is generated, and
the state variables become initialized to the particular values also when a Power On Reset is performed.
9. (Currently amended) A device comprising:
means for receiving periodic input pulses; and
means for counting the received input pulses to generate prescaled pulses, wherein
one prescaled pulse is generated for every Qth input pulse, wherein Q is a division modulus having a value depending on a value of a modulus control signal, and
when a prescaled pulse is generated from a selected input pulse, the modulus control signal is ignored at least until the onset of a next input pulse following the selected input pulse is received; and
a means for generating a reset signal in response to the prescaler receiving the Mth input pulse, wherein M is a preset integer, and
wherein a swallow counter changes the modulus control signal in response to a reset signal.

when the prescaler receives an Mth one of the input pulses, the modulus control signal changes value after the prescaler has already received the onset of the next input pulse, wherein M is a preset integer.

15. (Original) The method of claim 14, further comprising:
generating a divided down signal in response to the prescaler receiving the Mth input pulse;
generating a synchronized signal in response to the divided down signal; and
generating a fast clock signal in response to the synchronized signal, and
wherein the input periodic pulses are derived from the fast clock signal.

Claim 16 (canceled).

17. (Currently amended) The method of claim ~~14~~10, wherein
the state variables are encoded in signals generated by logical devices.
18. (Currently amended) The method of claim ~~14~~10, wherein
a selected one of the state variables is set equal to one at initialization, and
the modulus control signal is ORed with the signal encoding the selected state variable.
19. (Currently amended) The method of claim ~~14~~10, wherein
if a Power On Reset is performed, the state variables are also initialized to the same states as
when a prescaled pulse is generated.
20. (Currently amended) The method of claim ~~14~~10, wherein
the vector is made at least from state variables D2, D1, D0,
each of the state variables D2, D1, D0 is initialized with a value of one, and
updating the vector further includes: